

Fire



Weatherproof version

DATA
SHEET

Conventional Sounder Beacon

FL-RL-R-S / FL-RL-R-D

MCD524DB

FX004R / FX000WP

COOPER

This range of sounder beacons are available to complement purely audible alarms for use in areas either where people may be present who have impaired hearing or areas with high ambient noise levels.

The device offers an audible and a visual alarm combined together in one unit and require only a single installation point. This greatly reduces installation time and cost and is much less obtrusive than two separate devices.

Beacons have a high light output to maximise the attention attracting potential of the device.

Lower power LED variants are also available which offer a lower current consumption but have a consequently lower light output.

Benefits and Features

- > High output sounder beacon
- > Sounder and beacon with a single installation point
- > Unobtrusive low profile design
- > Volume control
- > Lockable base



Technical Specifications

Model	FL-RL-R-S / FX002CR	FL-RL-R-D / MCD524DB / FX000WP
Description	Sonder beacon	Sonder beacon - weatherproof
Operating voltage	18 to 30V dc	
Sound output	101dB(A) at 24V dc	
Current consumption	68mA at 24V dc	
Environmental rating	IP42. -10°C to +55°C	IP66. -10°C to +55°C
Physical		
Construction	Lens - Polycarbonate, Base - ABS	
Colour	Red	
Dimensions (Dia x D)	93mm x 92mm	93mm x 121mm
Weight	0.29kg	0.33kg
Compatibility	Conventional fire systems	

Product Codes

Conventional sounder beacon	FL-RL-R-S / FX002CR
Conventional sounder beacon - weatherproof	FL-RL-R-D / MCD524DB / FX000WP

Cooper Lighting and Safety

Wheatley Hall Road, Doncaster, South Yorkshire DN2 4NB

www.cooperfire.com

Sales

T: +44 (0)1302 303 999
 F: +44 (0)1302 303 333
 E: sales@cooperfire.com

Technical

T: +44 (0)1302 303 350
 F: +44 (0)1302 303 332
 E: techsupport@cooperfire.com

Export

T: +44 (0)1302 303 344
 F: +44 (0)1302 303 345
 E: export@cooperfire.com